

Rugged brass bodies with excellent corrosion resistance make these valves the ideal choice for arduous applications. Large and robust manual actuators are available together with air pilot actuators.

- Rugged valves for heavy duty applications
- Large and robust actuators for easy operation
- Excellent corrosion resistance
- Integral mounting holes
- Panel mounting versions



Operating information

Working temperature -40 °C to +70 °C

Working pressure Max 10 bar

Flow (Qmax): 380 l/min

For more information see www.parker.com/euro_pneumatic

Push button valves, VA13 Series - G $\frac{1}{8}$

Symbol	Actuator	Return	Operating force at 6 bar, N	Mounting	Order code
Hand actuated					
	Flush-Push button, red	Spring	32,5	Panel	VA13-HIS4
	Flush-Push button, black	Spring	32,5	Panel	VA13-HIS4A06
	Hand lever Held in 2 positions	Hand lever	8	Panel	VA13-HB24
	Hand lever Held in 2 positions	Hand lever	8	Side	VA13-HB2
	Button, red, 2 positions	Button	3	Panel	VA13-KL24
	Button, red, 2 positions	Spring	31,5	Panel	VA13-KS4
	Button, red, 2 positions	Button	3	Side	VA13-KL2
	Button, red, 2 positions	Spring	31,5	Side	VA13-KS
	Button, red, 2 positions	Knob/Air signal	6	Side	VA13-KL2A

Accessories for VA13/15HI... Series valves

	Description	Order code
	Diaphragm, black	9127359331
	Diaphragm, yellow	9127359332
	Mounting ring	9127359334

Push button valves, VA15 Series - G $\frac{1}{8}$ connection

Symbol	Actuator	Return	Operating force at 6 bar, N	Mounting	Order code
Hand actuated					
	Flush-Push button, red	Spring	34,5	Panel	VA15-HIS4
	Hand lever Held in 2 positions	Hand lever	9	Panel	VA15-HB24
	Hand lever Held in 3 positions closed centre position	Hand lever	9	Panel	VA15-HB34
	Hand lever Held in 3 positions vented centre position	Hand lever	9	Panel	VA15-XHB34
	Hand lever Held in 3 positions closed centre position	Hand lever	9	Panel	VA15-HC4
	Hand lever Held in 3 positions self centring vented centre position	Hand lever	9	Panel	VA15-XHC4
	Hand lever Held in 2 positions	Hand lever	9	Side	VA15-HB2
	Button, red, 2 positions	Button	5	Panel	VA15-KL24
	Button, red, 2 positions	Button	5	Side	VA15-KL2
	Air signal	Air signal	3/3	Side	VA15-AA
	Air signal	Spring	4/-	Side	VA15-AS

All 3/2 type VA13 valves can be connected either as normally closed 3/2 valve (NC) or normally open 3/2 valve (NO) as required, by connecting the primary air supply to port 1 or port 3

Dimensions

